



1MVA UPS POWER TRAILER

NETWORK PROTECTION

SURE POWER'S INDUSTRY LEADING POWER PROTECTION PRODUCTS ARE AVAILABLE TO MEET ALL OF YOUR CRITICAL INFRASTRUCTURE NEEDS.

STANDALONE AND MOBILE UPS SYSTEMS

READY FOR IMMEDIATE DEPLOYMENT TO YOUR FACILITY WITH ONE CALL TO SURE POWER. MOST EQUIPMENT SHIPS WITHIN (2) HOURS.

EMERGENCY RESPONSE

SURE POWER'S STAFF
OF FIELD SERVICE
TECHNICIANS ARE ONCALL 24 X 7 X 365 TO
MEET OUR CUSTOMER'S
DEMANDS.

1.800.455.0054

Ó

www.UPSRental.com

| | Trailer Data |
|--------------------------------------|--|
| Manufacturer: | Utility Trailer with Air-Ride Suspension |
| Total Length: | 44'L x 8.7'W x 13.5'h |
| Total Weight - Trailer and Contents: | 57,000 lbs |
| UF | PS Information |
| Manufacturer: | Toshiba |
| Series/Model: | Series 9000/T90S3S01MS6XSN |
| kVA Rating | 1,000 kVA |
| Output Power Factor: | 1.0 |
| Output kW Rating: | 1,000 kW |
| Input Voltage: | 480 VAC, 3 Ø, 60 HZ |
| Input Wiring: | 3W + Ground |
| | Dual Input (optional): 480VAC, 3Ø |
| | 1,600 Amp Input Feed Required |
| Output Voltage: | 480 VAC L-L, 3 Ø, 60 HZ |
| Output Wiring: | 3-Wire and Ground Rated at 1,600 AAC |
| | 1,203 Amps Maximum UPS Output Capacity |
| Wrap-Around Maintenance Bypass: | Yes |
| UPS B | attery Information |
| Battery Type: | EnerSys 12VDC, Monobloc, VRLA, Non-Spillable |
| Battery Watts Per Cell: | 540 WPC |
| Nominal DC Link Voltage: | 480 VDC |
| Number of Cells Per String: | 240 Cells |
| Number of Strings: | 6 Strings |
| Estimated Battery Run-Time: | 9.0 minutes @ 1,000 kW |
| Battery Disconnect: | 3,000 Each |
| HV | AC Information |
| Manufacturer: | Barc |
| Number of A/C Units: | |
| Capacity Per Unit: | 6 Tons |
| Total Tonnage: | 24 Tons |
| Monit | toring Information |
| HVAC Supervision Ambie | ent Temperature Discrete UPS Alarms |
| Cellula | ar Alarm Monitoring |
| Spare Batter | ies and Spare Parts Onboard |
| | ontact at Sure Power |

800.455.0054: Office | 215.375.4764: Cell | gmcneil@sure-power.com