



750KVA UPS POWER TRAILER

NETWORK PROTECTION

SURE POWER'S INDUSTRY LEADING POWER PROTECTION PRODUCTS ARE AVAILABLE TO MEET ALL OF YOUR CRITICAL INFRASTRUCTURE NEEDS.

STANDALONE AND MOBILE UPS SYSTEMS

READY FOR IMMEDIATE DEPLOYMENT TO YOUR FACILITY WITH ONE CALL TO SURE POWER. MOST EQUIPMENT SHIPS WITHIN (2) HOURS.

EMERGENCY RESPONSE

SURE POWER'S STAFF
OF FIELD SERVICE
TECHNICIANS ARE ONCALL 24 X 7 X 365 TO
MEET OUR CUSTOMER'S
DEMANDS.

1.800.455.0054

Ó

www.UPSRental.com

Trailer Data	
Manufacturer:	Utility Trailer with Air-Ride Suspension
Total Length:	44'L x 8.7'W x 13.5'H
Total Weight - Trailer and Contents:	52,000 lbs.
UP	S Information
Manufacturer:	Liebert
Series/Model:	Series 610/U39SA751AAAN113
kVA Rating	750 kVA
Output Power Factor:	0.9
Output kW Rating:	675 kW
Input Voltage:	480 VAC, 3 Ø, 60 HZ
Input Wiring:	3W + Ground
	Dual Input (optional): 480VAC, 3Ø
	1,200 Amp Input Feed Required
Output Voltage:	480 VAC L-L, 3 Ø, 60 HZ
Output Wiring:	3-Wire and Ground Rated at 1,200 AAC
	902 Amps Maximum UPS Output Capacity
Wrap-Around Maintenance Bypass:	Yes
UPS Ba	attery Information
Battery Type:	EnerSys 12VDC, Monobloc, VRLA, Non-Spillable
Battery Watts Per Cell:	540 WPC
Nominal DC Link Voltage:	480 VDC
Number of Cells Per String:	240 Cells
Number of Strings:	4 Strings
Estimated Battery Run-Time:	9.0 minutes @ 675 kW
Battery Disconnect:	Quantity (2) at 800 Amps Each
HVA	AC Information
Manufacturer:	Bard
Number of A/C Units:	4
Capacity Per Unit:	6 Tons
Total Tonnage:	24 Tons
Monito	oring Information
HVAC Supervision Ambie	nt Temperature Discrete UPS Alarms
Cellular	Alarm Monitoring
Spare Batterio	es and Spare Parts Onboard
Rental Co	ontact at Sure Power
	Gene McNeil

800.455.0054: Office | 215.375.4764: Cell | gmcneil@sure-power.com

