



## 160KVA UPS POWER TRAILER

### NETWORK PROTECTION

SURE POWER'S INDUSTRY LEADING POWER PROTECTION PRODUCTS ARE AVAILABLE TO MEET ALL OF YOUR CRITICAL INFRASTRUCTURE NEEDS.

.....

### STANDALONE AND MOBILE UPS SYSTEMS

READY FOR IMMEDIATE DEPLOYMENT TO YOUR FACILITY WITH ONE CALL TO SURE POWER. MOST EQUIPMENT SHIPS WITHIN (2) HOURS.

.....

### EMERGENCY RESPONSE

SURE POWER'S STAFF OF FIELD SERVICE TECHNICIANS ARE ON-CALL 24 X 7 X 365 TO MEET OUR CUSTOMER'S DEMANDS.

.....



**1.800.455.0054**

[www.UPSRental.com](http://www.UPSRental.com)

Trailer Data	
Manufacturer:	Conex Trailer
Total Length:	25.25'L x 8'W x 12.5'H
Total Weight - Trailer and Contents:	26,000 lbs.
UPS Information	
Manufacturer:	Emerson/Liebert
Series/Model:	NX/38SA200A0A00
kVA Rating	160 kVA
Output Power Factor:	0.9
Output kW Rating:	144 KW
Input Voltage:	480 VAC, 3 Ø
Input Wiring:	3W + Ground
	Single Input: 3Ø, 480 VAC
	233 Amps at 480 VAC
Output Voltage:	480VAC L-L, 3Ø
Output Wiring:	3W + Ground
	192 Amps Maximum Output Capacity
Wrap-Around Maintenance Bypass:	Yes
UPS Battery Information	
Battery Type:	C&D Technologies 12VDC, Monobloc, VRLA, Non-Spillable
Battery Watts Per Cell:	350 WPC
Nominal DC Link Voltage:	480 VDC
Number of Cells Per String:	240 Cells
Number of Strings:	2 Strings
Estimated Battery Run-Time:	16.0 minutes @ 144 kW
Battery Disconnect:	250 Amps
HVAC Information	
Manufacturer:	Bard
Number of A/C Units:	1
Capacity Per Unit:	3 Tons
Total Tonnage:	3 Tons
Monitoring Information	
HVAC Supervision   Ambient Temperature   Discrete UPS Alarms	
Cellular Alarm Monitoring	
Rental Contact at Sure Power	
Gene McNeil	
800.455.0054: Office   215.375.4764: Cell   <a href="mailto:gmcneil@sure-power.com">gmcneil@sure-power.com</a>	