



## 300KVA UPS POWER TRAILER

## NETWORK PROTECTION

SURE POWER'S INDUSTRY LEADING POWER PROTECTION PRODUCTS ARE AVAILABLE TO MEET ALL OF YOUR CRITICAL INFRASTRUCTURE NEEDS.

## STANDALONE AND MOBILE UPS SYSTEMS

READY FOR IMMEDIATE DEPLOYMENT TO YOUR FACILITY WITH ONE CALL TO SURE POWER. MOST EQUIPMENT SHIPS WITHIN (2) HOURS.

## EMERGENCY RESPONSE

SURE POWER'S STAFF
OF FIELD SERVICE
TECHNICIANS ARE ONCALL 24 X 7 X 365 TO
MEET OUR CUSTOMER'S
DEMANDS.

1.800.455.0054

Ó

www.UPSRental.com

	Frailer Data
Manufacturer:	Utility Trailer with Air-Ride Suspension
Total Length:	42'L x 8.6'W x 13.5'H
Total Weight - Trailer and Contents:	42,000 lbs.
	S Information
Manufacturer:	Emerson/Liebert
Series/Model:	Series 610/U39SA300AAAB426
kVA Rating	300 kVA
Output Power Factor:	0.8
Output kW Rating:	240 KW
Input Voltage:	480 VAC, 3 Ø, 60 HZ
Input Wiring:	3W + Ground
	Dual Input (optional): 480VAC, 3Ø
	400 Amp Input Feed Required
Output Voltage:	480 VAC L-L, 3 Ø, 60 HZ
Output Wiring:	3 or 4-Wire + Ground
	361 Amps Maximum UPS Output Capacity
Wrap-Around Maintenance Bypass:	Yes
UPS Ba	attery Information
Battery Type:	EnerSys 12VDC, Monobloc, VRLA, Non-Spillable
Battery Watts Per Cell:	400 WPC
Nominal DC Link Voltage:	480 VDC
Number of Cells Per String:	240 Cells
Number of Strings:	3 Strings
Estimated Battery Run-Time:	17.0 minutes @ 40 Kw
Battery Disconnect:	800 Amps
HVA	AC Information
Manufacturer:	Bard
Number of A/C Units:	2
Capacity Per Unit:	6 Tons
Total Tonnage:	12 Tons
Monito	oring Information
HVAC Supervision   Ambie	nt Temperature   Discrete UPS Alarms
Cellular	Alarm Monitoring
Spare Batterie	es and Spare Parts Onboard
Rental Co	ntact at Sure Power
G	Gene McNeil

800.455.0054: Office | 215.375.4764: Cell | gmcneil@sure-power.com