



50KVA INDUSTRIAL POWER TRAILER

NETWORK PROTECTION

SURE POWER'S INDUSTRY LEADING POWER PROTECTION PRODUCTS ARE AVAILABLE TO MEET ALL OF YOUR CRITICAL INFRASTRUCTURE NEEDS.

STANDALONE AND MOBILE UPS SYSTEMS

READY FOR IMMEDIATE DEPLOYMENT TO YOUR FACILITY WITH ONE CALL TO SURE POWER. MOST EQUIPMENT SHIPS WITHIN (2) HOURS.

EMERGENCY RESPONSE

SURE POWER'S STAFF OF FIELD SERVICE TECHNICIANS ARE ON-CALL 24 X 7 X 365 TO MEET OUR CUSTOMER'S DEMANDS.

1.800.455.0054

www.UPSRental.com

Trailer Data	
Manufacturer:	Conex Trailer
Total Length:	25.25'L x 8'W x 12.5'H
Total Weight - Trailer and Contents:	25,000 lbs.
UPS Information	
Manufacturer:	Emerson/Liebert
Series/Model:	EXCOR Apodyc/120-50KNT-120-1-PWM
kVA Rating	50 kVA
Output Power Factor:	0.8
Output kW Rating:	40 KW
Input Voltage:	480 VAC, 3 Ø
Input Wiring:	3W + Ground
	Dual Input: 480 VAC, 3Ø and 120 VAC, 1Ø
	100 Amps UPS Input and 425 Amp Bypass Input
Output Voltage:	120 VAC L-N, 1Ø
Output Wiring:	2W + Ground
	417 Amps Maximum Output Capacity
Wrap-Around Maintenance Bypass:	Yes
UPS Battery Information	
Battery Type:	C&D 12VDC, Monobloc, VRLA, Non-Spillable
Battery Watts Per Cell:	540 WPC
Nominal DC Link Voltage:	120 VDC
Number of Cells Per String:	60 Cells
Number of Strings:	4 Strings
Estimated Battery Run-Time:	68.0 minutes @ 40 kW
Battery Disconnect:	400 Amps
HVAC Information	
Manufacturer:	Bard
Number of A/C Units:	2
Capacity Per Unit:	3 Tons
Total Tonnage:	6 Tons
Monitoring Information	
HVAC Supervision Ambient Temperature Discrete UPS Alarms	
Cellular Alarm Monitoring	
Spare Batteries and Spare Parts Onboard	
Rental Contact at Sure Power	
Gene McNeil	
800.455.0054: Office 215.375.4764: Cell gmccneil@sure-power.com	