



80KVA UPS POWER TRAILER

NETWORK PROTECTION

SURE POWER'S INDUSTRY LEADING POWER PROTECTION PRODUCTS ARE AVAILABLE TO MEET ALL OF YOUR CRITICAL INFRASTRUCTURE NEEDS.

STANDALONE AND MOBILE UPS SYSTEMS

READY FOR IMMEDIATE DEPLOYMENT TO YOUR FACILITY WITH ONE CALL TO SURE POWER. MOST EQUIPMENT SHIPS WITHIN (2) HOURS.

EMERGENCY RESPONSE

SURE POWER'S STAFF OF FIELD SERVICE TECHNICIANS ARE ON-CALL 24 X 7 X 365 TO MEET OUR CUSTOMER'S DEMANDS.

1.800.455.0054

www.UPSRental.com

Trailer Data	
Manufacturer:	Conex Trailer
Total Length:	25.25'L x 8'W x 12.5'H
Total Weight - Trailer and Contents:	25,000 lbs.
UPS Information	
Manufacturer:	Emerson/Liebert
Series/Model:	Npower/375A080A0A6SA50
kVA Rating	80 kVA
Output Power Factor:	0.8
Output kW Rating:	64 kW
Input Voltage:	480 VAC at 60 HZ
Input Wiring:	3Ø, 3-Wire + Ground
	Single Input at 480 VAC
	175 Amp s at 480 VAC L-L
Output Voltage:	480 VAC L-L, 3 Ø, 60 HZ
Output Wiring:	3-Wire + Ground
	96 Amps Maximum UPS Output Capacity
Wrap-Around Maintenance Bypass:	Yes
UPS Battery Information	
Battery Type:	EnerSys 12VDC, Monobloc, VRLA, Non-Spillable
Battery Watts Per Cell:	205 WPC
Nominal DC Link Voltage:	480 VDC
Number of Cells Per String:	240 Cells
Number of Strings:	2 Strings
Estimated Battery Run-Time:	25.0 minutes @ 64 kW
Battery Disconnect:	225 Amps
HVAC Information	
Manufacturer:	Bard
Number of A/C Units:	1
Capacity Per Unit:	3 Tons
Total Tonnage:	3 Tons
Monitoring Information	
HVAC Supervision Ambient Temperature Discrete UPS Alarms	
Cellular Alarm Monitoring	
Spare Batteries and Spare Parts Onboard	
Rental Contact at Sure Power	
Gene McNeil	
800.455.0054: Office 215.375.4764: Cell gmccneil@sure-power.com	